


SPECIFICATION

Wattage:	30W
Supply voltage:	200-240v 50/60Hz
Ingress protection IP:	IP44
Impact protection IK:	IK00
Colour temperature:	4000K/5500K
Driver:	LiFud
Chip:	Samsung
Power factor:	>0.9
Lifetime @ L70:	50 000hrs
Diffuser:	Arcylic
Weight:	3600g




DESCRIPTION

An energy efficient, flicker free 30w LED panel has a high luminaire efficacy of above 120lm/w for all available colour temperatures.

Easy to install and designed with a white housing for discreet integration into ceiling grids.

IES/LDT files available on request

PHOTOMETRIC



FURTHER INFORMATION

Installation type: Recessed
Housing Material: Aluminium
Housing Colour: White

Available on request;
Dimming: DALI, Triac, 1-10v
Emergency: 3hrs

Accessories;
Suspension Kit
Recessed Mounting Clips
Surface Mounting Kit

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminous Efficacy(lm/W)	Beam Angle	Dimensions L W H (mm)
30	3700	4000	>80	123	120°	595 x 595 x 9.8
30	3800	5500	>80	126	120°	595 x 595 x 9.8

TECHNICAL DRAWINGS

