

SPECIFICATION

Wattage:	17W/25W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP20/54
Impact protection IK:	IK04 (Opal)/IK07 (Tempered Glass)
Colour temperature:	3000K/4000K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	60 000hrs
Diffuser:	No Diffuser/Tempered Glass/Opal
Weight:	800g




DESCRIPTION

The Allied COB Downlight NL is a traditional LED downlight with three choices of diffusers (Opal, Tempered Glass and No diffuser) for most applications.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Die cast Aluminium
Colour: Black/White/Grey

Available on request;
Dimming: DALI, 1-10V, Triac
Emergency: 3hrs
IP20 and IP54

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W Cutout(mm)
17	2280	4000	>80	134	120°	105 x ø230 x ø218
25	2900	4000	>80	116	120°	105 x ø230 x ø218

TECHNICAL DRAWINGS

