

SPECIFICATION

Wattage:	20W/ 30W/ 49W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP65
Impact protection IK:	IK08
Colour temperature:	4000K/ 6500K
Driver:	GE
Chip:	GE
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Acrylic




DESCRIPTION

This fixture has an attractive, neutral aesthetics that makes it suitable for applications in both commercial, residential and industrial environments. It is an energyefficient, low maintenance alternative to traditional fluorescent waterproof fixtures.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface

Body: Polycarbonate
Colour: White

Available on request;
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
20	2500	4000	>80	125	125°	1170 x 66 x 63
30	3800	4000	>80	126	125°	1170 x 66 x 63
30	3650	4000	>80	121	125°	1470 x 66 x 63
49	6200	4000	>80	126	125°	1470 x 66 x 63

TECHNICAL DRAWINGS

