

## SPECIFICATION

Wattage:	28W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP44
Impact protection IK:	IK00
Colour temperature:	4000K/4700K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	40 000hrs
Diffuser:	Acrylic
Weight:	4800g




## DESCRIPTION

Presence detectors ensure areas are only lit when occupied and are therefore one of the best ways to significantly reduce running costs. The integrated driver technology uses microwaves to detect presence through the back of the LED panel controlling the LED panel when occupancy is detected.

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Recessed, Surface, Suspended

Body: Aluminium  
Colour: Silver trim

Available on request;  
Dimming: Microwave, DALI, Triac, 1-10V  
Emergency: 3hrs

Daylight harvesting sensor

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
28	3000	4000	≥80	107	120°	595 x 595 x 9

## TECHNICAL DRAWINGS

