

## SPECIFICATION

Wattage:	36W
Supply voltage:	200-240V 50/60Hz
Ingress protection IP:	IP44
Impact protection IK:	IK00
Colour temperature:	3000K/4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Acrylic




## DESCRIPTION

Allied Beacon Panel is a slim high lumen output panel with a microwave sensor to allow the luminaire to only be lit when needed to increase savings and duration. The sensor utilises a 'twist and lock' connection and is time delay and distance adjustable. An energy efficient, flicker free LED panel that has been specifically designed for schools and offices with a unified glare rating of less than 19 (UGR<19). LG05:Lighting for education and LG07:Lighting for offices compliant.

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Recessed, Surface mounting

Body: Aluminium  
Colour: Silver grey

Available on request;  
Dimming: DALI, Triac, 1-10V  
Emergency: 3hrs

300mm x 1200mm  
600mm x 1200mm

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
36	3300	4000	≥80	81	120°	595 x 595 x 12.5

## TECHNICAL DRAWINGS

