

## SPECIFICATION

Wattage:	100W/150W/200W/240W
Supply voltage:	220-240V 47-63Hz
Ingress protection IP:	IP65
Impact protection IK:	IK06
Colour temperature:	5000K
Driver:	Branded
Chip:	3030 SMD
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate
Weight:	4420g




## DESCRIPTION

The Circular High Bay range has a 1-10V dimmability feature as standard, providing further energy savings by connecting the lamps to remote movement or daylight sensors.

Supplied with 1m cable lead for easy installation. Ideal for warehouses, assembly plants, showrooms and retail premises.

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Suspended

Body: Aluminium  
Colour: Black

Available on request:  
Dimming: 1-10V

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L Dia (mm)
100	12000	5000	>80	120	50/110°	204 x ø362
150	18000	5000	>80	120	50/110°	204 x ø362
200	24000	5000	>80	120	50/110°	204 x ø362
240	26200	5000	>80	109	50/110°	204 x ø362

## TECHNICAL DRAWINGS

