

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66, IP68 & IP69K
Impact protection IK:	IK10
Colour temperature:	3000K/ 4000K/ 5000K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L80B50:	50 000hrs
Diffuser:	Polycarbonate




DESCRIPTION

The Allied IP68 Linear S is an extremely protected fitting with an IK rating of IK10 and an IP rating of IP66, IP68 and also IP69K. Providing a high lumen per watt. With a simple plug & play installation by disconnectable plug, this fitting is also suitable for repeated switching on and off and also long maintenance intervals. Resistant to external UV-rays, Very good resistance to oils and hydrocarbons

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface

Body: Polycarbonate
Colour: Chrome

Available on request;
Dimming: DALI
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L H Dia (mm)
16	1850	4000	>80	115	120°	708 x 123 x ø100
23	2775	4000	>80	120	120°	1018 x 123 x ø100
31	3700	4000	>80	119	120°	1318 x 123 x ø100
39	4625	4000	>80	118	120°	1618 x 123 x ø100
46	5550	4000	>80	120	120°	1850 x 123 x ø100

TECHNICAL DRAWINGS

