

## SPECIFICATION

Wattage:	100W/150W/200W
Supply voltage:	100-277V 50/60Hz
Ingress protection IP:	IP65
Impact protection IK:	IK00
Colour temperature:	3000K/4000K/5000K/6000K
Driver:	Refond SMD2835
Chip:	Refond SMD2835
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Acrylic PMMA
Weight:	3200g/4100g/5200g/5400g




## DESCRIPTION

The Allied Linear Hi-Bay F is specially designed for manufacturing areas, warehouses, production lines and high halls. The unique and stylish design fits perfectly in modern industrial environments.

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Suspended, Surface

Body: Die-cast Aluminium  
Colour: Silver & Blue

Available on request;  
Dimming: 1-10V, DALI  
Emergency: 3hrs  
Sensor: Microwave motion  
CRI 90

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
100	13500	4000	>80	135	110°	605 x 138 x 122
150	20000	4000	>80	133	110°	905 x 138 x 122
150	22000	4000	>80	146	110°	1205 x 138 x 122
200	27000	4000	>80	135	110°	1205 x 138 x 122

## TECHNICAL DRAWINGS

