

SPECIFICATION

| | |
|------------------------|------------------|
| Wattage: | 14W/ 23W |
| Supply voltage: | 220-240V 50/60Hz |
| Ingress protection IP: | IP20 |
| Impact protection IK: | IK00 |
| Colour temperature: | 3000K/ 4000K |
| Driver: | Osram |
| Chip: | Osram |
| Power factor: | >0.9 |
| Lifetime @ L70B50: | 50 000hrs |
| Diffuser: | Glass |
| Weight: | 1100g |




DESCRIPTION

A decorative downlight luminaire for suspended ceilings.
A decorative alternative to the standard LED downlight.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Aluminum
Colour: White

Available on request;
Dimming: DALI
Emergency: 3hrs, DALI
Full matt Glass, Full transparent glass,
Central Matted glass.

AVAILABLE OPTIONS

| Rated power(W) | Lumens (lm) | Colour Temperature (K) | CRI | Luminous Efficacy(lm/W) | Beam Angle | Dimensions W H Cutout (mm) |
|----------------|-------------|------------------------|-----|-------------------------|------------|----------------------------|
| 14 | 1700 | 4000 | >82 | 121 | 30°/72° | ø212 x 140 x ø170 |
| 23 | 2650 | 4000 | >82 | 115 | 30°/72° | ø212 x 140 x ø170 |

TECHNICAL DRAWINGS

