

### SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP65
Impact protection IK:	IK04
Colour temperature:	3000K/4000K/6500K
Driver:	Osram
Chip:	Osram
Power factor:	>0.9
Lifetime @ L70:	50 000hrs
Diffuser:	Tempered Glass




### DESCRIPTION

The Allied Floodlight LV is a perfect replacement for floodlights with halogen lamps. Perfect for applications such as car parks, underpasses, garages, building facades and construction areas. The weight is optimised due to its compact design. In all it is a very homogenous light.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Bracket

Body: Aluminium  
Colour: Black/White

Available on request;  
Sensor: PIR

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
10	800	4000	>80	80	100°	117 x 127 x 39
20	2100	4000	>80	105	100°	167 x 155 x 44
50	5250	4000	>80	105	100°	187 x 216 x 62
90	10000	4000	>80	110	100°	243 x 253 x 93
135	15000	4000	>80	110	100°	269 x 298 x 128
180	20000	4000	>80	110	100°	328 x 362 x 125

### TECHNICAL DRAWINGS

