

### SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP65
Impact protection IK:	IK08
Colour temperature:	4000K/5700K
Driver:	Osram
Chip:	Osram
Power factor:	>0.95
Lifetime @ L70:	100 000hrs
Diffuser:	Tempered Glass




### DESCRIPTION

The Allied Pro-Flood Mini L is an modern architectural flood light, using a powerful Osram chip and driver, giving out a high lumens per watt.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Adjustable Bracket

Body: High pressure die-cast Aluminium  
Colour: Grey

Available on request;  
Dimming: DALI, 1-10v  
Beam Angles: Asymmetric-narrow,  
asymmetric-wide

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
25	3300	4000	>70	132	25°/50°	272 x 238 x 73
45	5500	4000	>70	122	25°/50°	272 x 238 x 73
54	6450	4000	>70	119	25°/50°	272 x 238 x 73
70	7700	4000	>70	110	25°/50°	272 x 238 x 73

### TECHNICAL DRAWINGS

