

### SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66
Impact protection IK:	IK09
Colour temperature:	4000K/5700K
Driver:	Osram
Chip:	Osram
Power factor:	>0.95
Lifetime @ L80B10:	80 000hrs
Diffuser:	Glass
Weight:	6800g




### DESCRIPTION

Modern design LED Streetlight, offered in a number of different wattages with different dimming options and can adapted to both side and bottom mounting.

Lateral surface wind exposed.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

- Mounted: Bracket
- Body: High pressure die-cast Aluminum
- Colour: Gray/Graphite
- Available on request:**
- Dimming: DALI, 1-10V Dim, LLOC, Twilight Sensor.
- \*Type of Optic**
- 02 - Express Roads
- 03 - Local Roads
- 04 - Town Roads
- 05 - Residential Areas
- 06 - Pedestrian Crossings, Right side, Left Side
- 07 - Area Lighting
- 08 - Town & Local Roads

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
29	3150	5700	>70	109	Optic Type*	550 x 250 x 100
37	4100	5700	>70	111	Optic Type*	550 x 250 x 100
55	6100	5700	>70	111	Optic Type*	550 x 250 x 100
80	9550	5700	>70	119	Optic Type*	550 x 250 x 100
106	12500	5700	>70	118	Optic Type*	550 x 250 x 100

### TECHNICAL DRAWINGS



Reducers

