

SPECIFICATION

Wattage:	16W/20W/29W/35W/46W/56W/70W
Supply voltage:	24-48V, 220-240V 50/60Hz
Ingress protection IP:	IP66
Impact protection IK:	IK09
Colour temperature:	3000K/4000K
Driver:	Branded
Chip:	LED GO!
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate




DESCRIPTION

The Allied Saturn LE is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface, Suspended

Body: Polycarbonate
Colour: Grey

Available on request;
Dimming: DALI
Emergency: 3hrs
Sensor: Microwave

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
16	2500	4000	>80	156	120°	1152 x 85 x 80
20	2700	4000	>80	135	120°	1152 x 80 x 85
29	4500	4000	>80	155	120°	1152 x 85 x 80
46	7400	4000	>80	160	120°	1152 x 85 x 80
56	9000	4000	>80	160	120°	1152 x 85 x 80
35	5500	4000	>80	157	120°	1432 x 85 x 80
43	7000	4000	>80	162	120°	1432 x 85 x 80
70	10900	4000	>80	155	120°	1432 x 85 x 80

