

### SPECIFICATION

Wattage:	32W/44W/64W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP54
Impact protection IK:	IK08
Colour temperature:	3000K/4000K
Driver:	Branded
Chip:	Branded
Power factor:	>0.9
Lifetime @ L70:	50 000hrs
Diffuser:	PMMA
Weight:	4300g/5300g(with frost roof)




### DESCRIPTION

A range of decorative post top lights, available with a choice of two diffuser designs and an aluminium canopy. The chassis is made of injection moulded PC and is attached to the diffuser with the help of a quick lock system. Post top installation with three screws on poles Ø60mm.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Post Top

Body: Injection moulded PC  
Colour: Black

Available on request;  
High frequency control gear  
Diffuser: PC bowl, Clear diffuser, Mat Coated.  
Reflector: Stainless steel reflector

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions D H (mm)
32	3153	4000	>80	98	220°	Ø400 x 510
44	4491	4000	>80	102	220°	Ø400 x 510
64	6306	4000	>80	98	220°	Ø400 x 510

### TECHINCAL DRAWINGS

