

SPECIFICATION

Wattage:	70W/ 88W/ 104W
Supply voltage:	230V 50Hz
Ingress protection IP:	IP68
Impact protection IK:	IK10
Colour temperature:	6500K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate/Methacrylate




DESCRIPTION

A superior range of IP68 food factory LED luminaires. Constructed from a clear polycarbonate/methacrylate composite cylinder, secured by stainless steel endcaps and fastenings. Suitable for use in most food manufacturing and storage installations where efficiency is important.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface

Body: Steel
Colour: Chrome

Available on request:
Dimming: DALI

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
70	7400	6500	>80	105	120°	1295 x ø133 x 158
88	9250	6500	>80	105	120°	1595 x ø133 x 158
104	11100	6500	>80	106	120°	1850 x ø133 x 158

TECHNICAL DRAWINGS

