

SPECIFICATION

Wattage:	10W/14W/16W/20W
Supply voltage:	230V 50Hz
Ingress protection IP:	IP65
Impact protection IK:	IK08
Colour temperature:	3000K/4000K
Driver:	Osram
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate
Weight:	2500g/2600g




DESCRIPTION

A non-corrosive vandal resistant luminaire. IP65 - water and dust protection for use in adverse conditions. The diffuser is made of impact resistant UV stable polycarbonate. Suitable for surface mounting on the walls or ceiling. Outdoor. Building exteriors and other areas.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface

Body: Die-cast Aluminium
Colour: Dark Grey

Available on request;
Dimming: Switch Control, DALI, Dimmable Ballast
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W (mm)
Without Louver						
8	423	4000	>80	54	180°	ø265 x 90
14	1173	4000	>80	83	180°	ø265 x 90
14	1252	4000	>80	89	180°	ø360 x 130
20	1759	4000	>80	87	180°	ø360 x 130
With Louver						
8	325	4000	>80	40	180°	ø265 x 100
11	677	4000	>80	61	180°	ø265 x 100
10	642	4000	>80	64	180°	ø360 x 145
14	902	4000	>80	64	180°	ø360 x 145

TECHNICAL DRAWINGS



Louver