

### SPECIFICATION

Wattage:	21W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP40
Impact protection IK:	IK04
Colour temperature:	4000K/6000K
Driver:	Branded
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	30 000hrs
Diffuser:	Acrylic



### DESCRIPTION

Measuring 295mm x 595mm, this IP40 rated 21W panel light is ideal for replacing fluorescent T8/T5 tubes in both commercial and domestic settings. They are a popular lighting choice for hotels, factories, offices, schools, colleges, hospitals and the like. Energy use will be reduced by up to 65% and you'll notice a dramatic improvement in light quality.

### PHOTOMETRIC

### FURTHER INFORMATION

Mounting: Recessed, Suspended, Surface (Kit sold separately)

Body: Aluminium  
Colour: White Trim, Silver Trim

Available on request;  
Dimming: DALI, 1-10V  
Emergency: 3hrs

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W (mm)
21	2100	4000	>80	100	120°	295 x 595

### TECHNICAL DRAWINGS

