

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP40/44
Impact protection IK:	IK04
Colour temperature:	3000K/4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate




DESCRIPTION

A surface LED luminaire with translucent micro-linear diffuser and low modern profile.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface


Body: Steel Sheet
Colour: White

Available on request;
Dimming: DALI, Switch Dimming
Emergency: 3hrs, DALI
Sensor: Microwave

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
11	1227	4000	>80	112	120°	595 x 90 x 85
15	1723	4000	>80	114	120°	595 x 90 x 85
21	2455	4000	>80	119	120°	595 x 150 x 60
29	3446	4000	>80	120	120°	595 x 150 x 60
22	2591	4000	>80	118	120°	1195 x 90 x 85
30	3637	4000	>80	120	120°	1195 x 90 x 85
41	5182	4000	>80	125	120°	1195 x 150 x 60
61	7274	4000	>80	120	120°	1195 x 150 x 60
28	3273	4000	>80	118	120°	1495 x 90 x 85
38	4594	4000	>80	120	120°	1495 x 90 x 85
52	6545	4000	>80	125	120°	1495 x 150 x 60
77	9189	4000	>80	120	120°	1495 x 150 x 60

TECHNICAL DRAWINGS



L, mm	W, mm	H, mm
595	90	60
	150	85
1195	90	60
	150	85
1495	90	60
	150	85