

SPECIFICATION

Wattage:	10W/ 14W
Supply voltage:	230V 50Hz
Ingress protection IP:	IP65
Impact protection IK:	IK08
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Thermoplastic with sealing gasket and screw fixings




DESCRIPTION

The Allied Indurate N is an IP rated Surface mounted LED luminaire with a rounded profile along with a mechanical impact resistance of IK08.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface

Body: UV Stable Thermoplastic with white powder coated steel reflector
Colour: White, Black

Available on request;
Dimming: DALI, Switch dimming, 1-10V
Emergency: 3hrs, DALI 3hrs, Self-test
Control Gear: High frequency
Sensor: Microwave, Corridor, open area and stair case functions.

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
10	1112	3000	>80	111	120°	ø295 x 100
14	1554	3000	>80	111	120°	ø295 x 100
10	1172	4000	>80	117	120°	ø295 x 100
14	1638	4000	>80	117	120°	ø295 x 100

TECHNICAL DRAWINGS

