

SPECIFICATION

Wattage:	12W/16W/22W
Supply voltage:	200-240V AC 50/60Hz
Ingress protection IP:	IP44
Impact protection IK:	IK04
Colour temperature:	3000K/4000K/5500K
Driver:	Meanwell/ Tridonic
Chip:	Samsung
Power factor:	>0.92
Lifetime @ L70B50:	50 000hrs
Diffuser:	Acrylic
Weight:	500g/800g/1100g




DESCRIPTION

A circular LED panel which is easy to install with a white housing for discreet integration in to ceilings. The solid construction of this unit offers both uniformed light distribution as well as maintenance free operation.

These circular panels come with multiple driver options a powerful samsung chip and its available in three different colour temperatures.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Aluminium
Colour: White

Accessories:
Dimming: DALI, Triac, 1-10v
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminous Efficacy(lm/W)	Beam Angle	Dimensions W Cutout (mm)
Lucid 18;						
12	1100	4000	>80	93.7	120°	180 x Ø160
Lucid 24;						
16	1550	4000	>80	96.8	120°	240 x Ø220
Lucid 30;						
22	2000	4000	>80	90.9	120°	300 x Ø280

TECHNICAL DRAWINGS

