

SPECIFICATION

Wattage:	Various
Supply voltage:	230V 50Hz
Ingress protection IP:	IP44
Impact protection IK:	IK04
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Microprismatic




DESCRIPTION

A new concept of recessed mounted LED luminaires with microprismatic or opal diffuser for most commercial lighting applications.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed, Surface, Burgess

Body: Aluminium
Colour: White

Available on request;
Dimming: DALI, Switch
Emergency: DALI, 3hrs
Tunable White
Bluetooth Unit for wireless control via mobile device

AVAILABLE OPTIONS

Rated Power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
11	1213	4000	>80	110	120°	595 x 295 x 55
15	1703	4000	>80	113	120°	595 x 295 x 55
20	2433	4000	>80	121	120°	595 x 295 x 55
20	2623	4000	>80	131	120°	495 x 495 x 55
31	3698	4000	>80	119	120°	495 x 495 x 55
39	5246	4000	>80	134	120°	495 x 495 x 55
58	7869	4000	>80	135	120°	495 x 495 x 55
20	2623	4000	>80	131	120°	595 x 595 x 55
31	3698	4000	>80	119	120°	595 x 595 x 55
39	5246	4000	>80	134	120°	595 x 595 x 55
58	7869	4000	>80	135	120°	595 x 595 x 55
19	2570	4000	>80	135	120°	1195 x 295 x 55
26	3497	4000	>80	134	120°	1195 x 295 x 55
39	5246	4000	>80	134	120°	1195 x 295 x 55
36	5140	4000	>80	143	120°	1195 x 595 x 55
51	6994	4000	>80	137	120°	1195 x 595 x 55
77	10492	4000	>80	136	120°	1195 x 595 x 55