

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP40/44
Impact protection IK:	IK05
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	PMMA, Microprismatic




DESCRIPTION

A decorative recessed LED luminaire with a square opal diffuser for an especial working environment.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed, Surface

Body: Stee Sheet
Colour: White

Available on request;
Dimming: DALI, Switch, 1-10V
Emergency: 3hrs, DALI, Selftest
Sensor: Corridor Function, Microwave

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
31	3144	4000	>80	103	120°	595 x 595 x 70
45	4416	4000	>80	98	120°	595 x 595 x 70
61	6311	4000	>80	104	120°	595 x 595 x 70
31	3144	4000	>80	103	120°	1195 x 595 x 70
45	4416	4000	>80	98	120°	1195 x 595 x 70
61	6311	4000	>80	104	120°	1195 x 595 x 70

TECHNICAL DRAWINGS

