

## SPECIFICATION

Wattage:	136W/ 204W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP20
Impact protection IK:	IK08
Colour temperature:	3000K/4000K
Driver:	Tridonic
Chip:	Zhaga Book 7
Power factor:	>0.95
Lifetime @ L80B10:	72 000hrs
Diffuser:	Polycarbonate




## DESCRIPTION

Utilising refractor lens control to provide an accurate distribution of light, Haze Linear Highbay is perfect for a host of application including Warehouses, Retail Outlets, Showrooms, Exhibition Venues, General Applications and Sports Halls (IK08 Compliant). Haze Linear Highbay offers the full benefit of class leading LED lighting; light quality, long service lifetime, excellent UGR performance, reduced energy consumption and maintenance.

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Suspended, Surface, Trunking and Gripple.

Body: Die-cast Aluminium  
Colour: White, Urban Graphite, Black

Available on request;  
Dimming: Digital Dimming, DALI, Switch Dimming  
Emergency: DALI, Self-test, 3hrs

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
136	23200	4000	>80	170	82°/112°	1135 x 279 x 59
204	34800	4000	>80	170	82°/112°	1695 x 279 x 59

## TECHNICAL DRAWINGS



1135 x 279 x 59mm



1695 x 279 x 59mm