

## SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66, IP68 & IP69K
Impact protection IK:	IK10
Colour temperature:	3000K/ 4000K/ 5000K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L80B50:	50 000hrs
Diffuser:	Polycarbonate




## DESCRIPTION

The Allied IP68 Linear S - High Powered is an extremely protected fitting with an IK rating of IK10 and an IP rating of IP66, IP68 and also IP69K. Providing a high lumen per watt. With a simple plug & play installation by disconnectable plug, this fitting is also suitable for repeated switching on and off and also long maintenance intervals. Resistant to external UV-rays, Very good resistance to oils and hydrocarbons

IES/LDT files available on request.

## PHOTOMETRIC



## FURTHER INFORMATION

Mounting: Surface

Body: Polycarbonate  
Colour: Chrome

Available on request;  
Dimming: DALI  
Emergency: 3hrs

## AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L H Dia (mm)
46	5550	4000	>80	120	120°	995 x 158 x ø133
63	7400	4000	>80	117	120°	1295 x 158 x ø133
78	9250	4000	>80	118	120°	1595 x 158 x ø133
92	11100	4000	>80	120	120°	1850 x 158 x ø133

## TECHNICAL DRAWINGS

