

SPECIFICATION

Wattage:	6W/ 9W/ 12W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP65 - Fire rated
Impact protection IK:	IK06
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Acrylic




DESCRIPTION

Allied Pro Spot 10 Static I downlights are built using a deep recessed COB LED light source, providing a beam that has softened edges for a luxurious effect.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Aluminium Alloy, Acrylic & Iron
Colour: White

Available on request;
Dimming: DALI, 1-10V, Switch Dimming
Emergency: DALI, Self-test, 3hrs
Fire Rating: 30, 60, 90 Minutes

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W Cutout(mm)
6	450	4000	>80	75	36°	70 x ø85 x ø70
9	740	4000	>80	82	55°	70 x ø85 x ø70
12	850	4000	>80	71	55°	70 x ø85 x ø70

TECHNICAL DRAWINGS

