

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66
Impact protection IK:	IK10
Colour temperature:	3000K/4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Polycarbonate
Weight:	2900g/3400g




DESCRIPTION

The Allied Linear Extreme Temperature N is a water and dust resistant IP66 luminaire for use in extreme temperature environments. The diffuser is an Opal UV stabilised IK10 polycarbonate. Suitable for temperatures from -40°C to +50°C.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface, Suspended


Body: Polycarbonate
Colour: Grey

Available on request;
Dimming: DALI, Switch Dimming, Corridor Function

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
38	5490	4000	>80	144	180°	1272 x 96 x 111
44	6175	4000	>80	140	180°	1272 x 96 x 111
53	8068	4000	>80	153	180°	1272 x 146 x 111
27	4086	4000	>80	152	180°	1572 x 96 x 111
34	5045	4000	>80	148	180°	1572 x 96 x 111
48	6863	4000	>80	144	180°	1572 x 96 x 111
55	7719	4000	>80	140	180°	1572 x 96 x 111
66	10085	4000	>80	153	180°	1572 x 146 x 111

TECHNICAL DRAWINGS



L, mm	W, mm	H, mm	D, mm
1277	96	111	700
	146		
1577	96		940
	146		