

SPECIFICATION

Wattage:	12W/24W/40W/48W/80W/96W
Supply voltage:	220-240V 50.60Hz
Ingress protection IP:	IP65
Impact protection IK:	IK00
Colour temperature:	3000K/4000K/6000K
Driver:	Meanwell
Chip:	Epistar
Power factor:	>0.9
Lifetime @ L70:	>35,000hrs
Diffuser:	Acrylic




DESCRIPTION

Allied Linear IP65 H LED Anti Corrosive fittings are designed to replace the traditional Anti corrosive fluorescent type.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Surface or Suspended

Body: Polycarbonate
Colour: Grey

Available on request;
Dimming: DALI, Corridor functions
Emergency: 3hrs
Sensor: Microwave Sensor

AVAILABLE OPTIONS

	Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H (mm)
Single;							
	12	1000	4000	>80	83	180°	660 x 93 x 100
	24	2400	4000	>80	100	180°	1270 x 93 x 100
	30	2900	4000	>80	96	180°	1565 x 93 x 100
	40	4500	4000	>80	112	180°	1840 x 93 x 100
Twin;							
	24	2000	4000	>80	83	180°	660 x 140 x 100
	48	4560	4000	>80	95	180°	1270 x 140 x 100
	60	5700	4000	>80	95	180°	1565 x 140 x 100
	80	8600	4000	>80	107	180°	1840 x 140 x 100

TECHNICAL DRAWINGS