

### SPECIFICATION

|                        |                       |
|------------------------|-----------------------|
| Wattage:               | Various               |
| Supply voltage:        | 220-240V 50/60Hz      |
| Ingress protection IP: | IP65                  |
| Impact protection IK:  | IK07                  |
| Colour temperature:    | 3000K/4000K           |
| Driver:                | Osram                 |
| Chip:                  | Osram                 |
| Power factor:          | >0.95                 |
| Lifetime @ L70B50:     | 50,000hrs             |
| Diffuser:              | Opal plexiglass (PLX) |
| Weight:                | 8000g                 |




### DESCRIPTION

Modern recessed luminaire for modular suspended ceilings for. An IP rating of IP65 protecting it against water jets and dust tight. Also with an IK rating of IK07 protecting it against 2 joules of impact.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Recessed

Body: Powder-painted steel sheet  
Colour: White

Available on request;  
Dimming: DALI

### AVAILABLE OPTIONS

| Rated power(W) | Lumens(lm) | Colour Temperature(K) | CRI | Luminaire Efficacy(lm/W) | Beam Angle | Dimensions L W H (mm) |
|----------------|------------|-----------------------|-----|--------------------------|------------|-----------------------|
| 39             | 3950       | 3000                  | >80 | 101                      | 120°       | 595 x 595 x 110       |
| 39             | 4150       | 4000                  | >80 | 106                      | 120°       | 595 x 595 x 110       |
| 74             | 8000       | 3000                  | >80 | 106                      | 120°       | 595 x 595 x 110       |
| 74             | 8100       | 4000                  | >80 | 106                      | 120°       | 595 x 595 x 110       |

### TECHNICAL DRAWINGS

