

SPECIFICATION

Wattage:	105W/138W/175W
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66
Impact protection IK:	IK07
Colour temperature:	4000K/5700K/6500K
Driver:	Osram
Chip:	CREE
Power factor:	>0.95
Lifetime @ L80:	100 000hrs
Diffuser:	Tempered Glass
Weight:	6500g




DESCRIPTION

Stylish lowbay luminaire useful for warehouses and industrial facilities.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Suspended, Surface (frame sold separately).

Body: High pressure die-cast aluminium
Colour: Grey

Available on request;
Dimming: DALI
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
105	13000	4000	≥80	124	55°/110°/120x40°	515 x 345 x 90
138	17950	4000	≥80	130	55°/110°/120x40°	515 x 345 x 90
175	22100	4000	≥80	126	55°/110°/120x40°	515 x 345 x 90

TECHNICAL DRAWINGS

