

### SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP66
Impact protection IK:	IK10
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L80B50:	75 000hrs
Diffuser:	Polycarbonate




### DESCRIPTION

The Allied Linear N is a dust and moisture proof IP66 LED fixture for high impact resistance. It is a surface luminaire designed to be fixed to ceilings of any type or suspended.

IES/LDT files available on request.

Emergency Information: All emergencies are in operation for 3 hours, please ensure emergency batteries have been charged for 24 hours.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Surface, Suspended

Body: Polycarbonate  
Colour: Grey

Available on request;  
Dimming: DALI, Switch control, Corridor Function  
Emergency: 3hrs, DALI  
Sensor: Microwave

### AVAILABLE OPTIONS

Rated power(W)	Lumens (EM)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
<b>2ft Single;</b>						
15	2017 (469)	4000	>80	134	120°	662 x 96 x 111
21	2745 (455)	4000	>80	130	120°	662 x 96 x 111
<b>2ft Twin;</b>						
17	2475 (507)	4000	>80	145	120°	662 x 146 x 111
27	4034 (521)	4000	>80	149	120°	662 x 146 x 111
<b>4ft Single;</b>						
22	3266 (518)	4000	>80	148	120°	1272 x 96 x 111
27	4036 (521)	4000	>80	149	120°	1272 x 96 x 111
38	5490 (504)	4000	>80	144	120°	1272 x 96 x 111
50	6829 (479)	4000	>80	137	120°	1272 x 96 x 111
<b>4ft Twin;</b>						
65	9547 (511)	4000	>80	146	120°	1272 x 146 x 111
<b>5ft Single;</b>						
27	4082 (528)	4000	>80	151	120°	1572 x 96 x 111
34	5045 (518)	4000	>80	148	120°	1572 x 96 x 111
48	6863 (497)	4000	>80	142	120°	1572 x 96 x 111
63	8537 (472)	4000	>80	135	120°	1572 x 96 x 111
<b>5ft Twin;</b>						
81	11934 (514)	4000	>80	147	120°	1572 x 146 x 111