

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP20/ IP54/ IP65
Impact protection IK:	IK06
Colour temperature:	3000K/ 4000K
Driver:	Branded
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	50 000hrs
Diffuser:	Variations




DESCRIPTION

A range of recessed wide beam LED downlight luminaires. Constructed from a round white painted die-cast aluminium twist and lock bezel and high efficiency reflector. Suitable for use in foyers, meeting rooms, corridors and other areas in commercial buildings and retail shops. An IP65 bezel is an optional attachment.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Die-cast Aluminium
Colour: White

Available on request;
Dimming: DALI
Emergency: 3hrs
Diffusers: IP54 clear, IP54 centre etched, IP54 fully etched, IP54 clean polycarbonate, IP54 opal polycarbonate, IP64 clear glass, IP65 opal polycarbonate, Halo Kit

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W Cutout(mm)
11	950	4000	>80	85	60°	ø195 x 160 x ø176
20	1861	4000	>80	90	60°	ø195 x 160 x ø176
30	2828	4000	>80	94	60°	ø195 x 160 x ø176
48	4436	4000	>80	91	60°	ø195 x 160 x ø176

TECHNICAL DRAWINGS

