

SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP40
Impact protection IK:	IK04
Colour temperature:	3000K/ 4000K
Driver:	Mitsubishi
Chip:	Branded
Power factor:	>0.95
Lifetime @ L70:	70 000hrs
Diffuser:	None




DESCRIPTION

The Allied Trumpet Downlight is a low glare light distribution 19 (UGR<19). LG05:Lighting for education and LG07:Lighting for offices compliant. With high efficacy and lumen output and a beautiful light distribution for use in areas including offices, conference rooms, retail spaces, foyers, corridors, hotels or restaurants.

IES/LDT files available on request.

PHOTOMETRIC



FURTHER INFORMATION

Mounting: Recessed

Body: Aluminium & PBT
Colour: White

Available on request;
Dimming: DALI
Emergency: 3hrs

AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions W H Cutout(mm)
15	1550	4000	>80	103	60°	ø170 x 102 x ø155
20	2200	4000	>80	110	65°	ø220 x 121 x ø205
30	3300	4000	>80	110	65°	ø220 x 121 x ø205

TECHNICAL DRAWINGS

