

### SPECIFICATION

Wattage:	Various
Supply voltage:	220-240V 50/60Hz
Ingress protection IP:	IP40
Impact protection IK:	IK05
Colour temperature:	3000K/ 4000K
Driver:	Tridonic
Chip:	Samsung
Power factor:	>0.95
Lifetime @ L80B50:	100 000hrs
Diffuser:	Double Parabolic




### DESCRIPTION

A recessed LED luminaire with double parabolic reflector for a glare-free lighting effect.

Louvre: double parabolic, UGR<19 glare protection.

IES/LDT files available on request.

### PHOTOMETRIC



### FURTHER INFORMATION

Mounting: Recessed

Body: Aluminium  
Colour: White

Available on request;  
Dimming: DALI, Switch, Corridor  
Emergency: 3hrs, DALI  
Sensor: Corridor Function  
RAL Colour

### AVAILABLE OPTIONS

Rated power(W)	Lumens (lm)	Colour Temperature (K)	CRI	Luminaire Efficacy(lm/W)	Beam Angle	Dimensions L W H(mm)
14.0	1774	4000	>80	127	120°	595 x 295 x 40
19.6	2541	4000	>80	130	120°	595 x 595 x 40
28.9	3658	4000	>80	127	120°	595 x 595 x 40
38.6	4878	4000	>80	127	120°	595 x 595 x 40
42.7	5401	4000	>80	127	120°	595 x 595 x 40
19.1	2541	4000	>80	133	120°	1195 x 295 x 40
28.9	3658	4000	>80	127	120°	1195 x 295 x 40
57.8	7317	4000	>80	127	120°	1195 x 595 x 40
86.7	10975	4000	>80	127	120°	1195 x 595 x 40

